

TOTAL COMFORT & CONTROL

AquaComfort IS THE MOST EFFICIENT AND ECONOMICAL SOLUTION TO HEAT YOUR POOL!

AquaComfort heat pumps are the result of over 25 years of continued innovation. We have designed, tested and manufactured the most efficient, economical heat pumps. Tens of thousands of pool owners across America get the most pleasure from their pools by heating with AquaComfort. No matter where you live, our solution delivers **more heat starting at lower temperatures**, without all the harmful emissions.

Engineered to capture more of the free heat from the surrounding air, we've innovated and perfected the science of pool heating. The Turboguard titanium heat exchanger is virtually immune to damage from unbalanced water chemistry. Our fan assembly uses less energy and runs essentially silent; a precision package that lasts longer while maintaining efficiency year after year.



Heat Pump Data

Model	ACT-750	ACT-1100	ACT-1250	ACT-1500	ACT-1750	ACT-1250HC
Compressor	SCROLL	SCROLL	SCROLL	SCROLL	SCROLL	SCROLL
Minimum Breaker Size	20	30	40	40	50	40
Voltage / Hertz / Phase	230 / 60 / 1	230 / 60 / 1	230 / 60 / 1	230 / 60 / 1	230 / 60 / 1	230 / 60 / 1
Water Flow (gpm)	15 - 50	20 - 70	20 - 70	20 - 70	20 - 70	20 - 70
Dimensions (L x W x H)	28" x 28" x 26"	39" x 30" x 32"	39" x 30" x 32"	39" x 30" x 32"	39" x 30" x 32"	39" x 30" x 32"
Shipping Weight	170 lbs	240 lbs	240 lbs	250 lbs	290 lbs	250 lbs
Performance** (BTU's)	57,000	93,000	108,000	128,000	135,000	103,000
Efficiency** (COP)	5.1	5.4	5.3	5.7	5.8	5.1

Performance** and Efficiency** are rated based on 80° air / 80° water / 80% humidity in accordance with AHRI standard 1160.

Recommended clearance access on service side is 24" and 18" on other three air intake sides.
Recommended minimum over head (top of unit) clearance is 48".